

2023 Transportation Conformity

Appendix 12.18: MoSERS Methodology and Calculation Descriptions

3.0 IMPROVED PUBLIC TRANSIT -- LIGHT RAIL

3.1 System/Service Expansion

Strategy: Increase ridership by providing new rail system services
Description: Expansion of transit system or service can include the addition of rail services through increased frequency or route extension. Bus or paratransit services can be expanded with new vehicles and/or route extensions.
Application: Large cities or communities with enough population density to support reasonably frequent transit service.

Project Year: 2023

Project Description:

Project Code:

Variables:	Source		NO _x	VOC
EF_B: Speed-based running exhaust emission factor for affected roadway before implementation (NO _x or VOC) (grams/mile) (<i>assume 34 mph, Light Duty Vehicles in all roadway types</i>)	MOVES3	EF_B:	0.11	0.04
EF_{TV}: Speed-based running exhaust emission factor for transit vehicle	DART	EF_{TV}:	0.00	0.00
F_{T,sov}: Percentage of people using a transit vehicle that previously were	MOSERS	F_{T,sov}:	0.40	0.40
N_{TR}: New transit ridership (<i>total ridership</i>)	Project Specific	N_{TR}:	17,490	17,490
TEF_{AUTO}: Auto trip-end emission factor (NO _x or VOC) (grams/trip)	MOVES3	TEF_{AUTO}:	0.37	0.47
TEF_{TV}: Transit vehicle trip-end emission factor (NO _x or VOC) (grams/trip)	DART	TEF_{TV}:	0.00	0.00
TL_w: Average auto trip length (to work) (miles)	COG Default	TL_w:	13.28	13.28
TL_{TV}: Route Length of the Transit Vehicle (miles)	DART	TL_{TV}:	0.00	0.00
VT_{TV}: Daily vehicle trips by transit vehicle	DART	VT_{TV}:	0.00	0.00
VT_R: Reduction in number of daily automobile vehicle trips		VT_R:	6996.00	6996.00
VMT_{TV/BUS}: Vehicle miles traveled by transit vehicle		VMT_{TV}:	0.00	0.00
VMT_R: Reduction in daily automobile VMT		VMT_R:	92906.88	92906.88
Conversion Factor: Convert grams per mile of emissions to pounds per mile of emissions		Conversion Factor:	453.60	453.60

Equation:			NO _x	VOC
A = VT_R * TEF_{AUTO} Reduction in auto start emissions from trips reduced		A:	2588.52	3288.12
B = VMT_R * EF_B Reduction in auto running exhaust emissions from VMT reductions		B:	10219.76	3716.28
C = VT_{TV} * TEF_{TV} Increase in emissions from additional train starts		C:	0.00	0.00
D = VMT_{TV} * EF_{TV} Increase in emissions from additional train running exhaust		D:	0.00	0.00
Where,				
VT _R = N _{TR} * F _{T,sov} Number of new transit riders multiplied by the percentage of riders		VT _R :	6996.00	6996.00
VMT _R = VT _R * TL _w Number of vehicle trips reduced multiplied by the average auto trip		VMT _R :	92906.88	92906.88
VMT _{TV/BUS} = VT _{TV} * TL _{TV} Number of vehicle trips reduced multiplied by the average transit route length.		VMT _{TV/BUS} :	0.00	0.00

Results:			NO _x	VOC
Daily Emission Reduction = (A + B - C - D) / Conversion Factor		Daily Emission Reduction (lbs/day) =	28.24	15.44
		Daily Emission Reduction (tons/day) =	0.01	0.01

Source: The Texas Guide to Accepted Mobile Source Emission Reduction Strategies, Texas Transportation Institute, August 2007

Part C and Part D are both equal to zero because the DART system utilizes electric light rail, which has zero-emission train equipment. Local assumptions are calculated from the Dallas-Fort Worth Regional Travel Model and professional judgment of the Dallas Area Rapid Transit and North Central Texas Council of Governments staff.

Shading denotes input variables specific to the project. Other variables are either standard for the program or calculated using these inputs.

Blue - Project Specific Input

Yellow - Assumptions

Green - Emission Factors

4.0 High-Occupancy Vehicle Facilities

4.1 Freeway HOV Facilities

Strategy: Reduction of emissions by decreasing VMT and increased average speeds on the lane.

Project Year: 2023

Description: Separate lanes on controlled access highways are created for vehicles containing a specified number of passengers. The lane may be concurrent flow, barrier/buffer separated, or have a separate right-of-way.

Project Description:

Application: Highways in areas of traffic congestion with sufficient available right-of-way.

Project Code:

<p>MOSERS Formula: Emission Benefit (lbs/day) = [A + B + C] (grams/day)/CF (grams/lbs)</p> <p>A= $V_{HOV} * (EF_b - EF_a) * L$</p> <p>B= $(V_{GP,B} * EF_b - V_{GP,A} * EF_a) * L$ "assume negligible"</p> <p>C= $V_{Tr} (TE_{Fauto} + EF_b * TL_w)$</p> <p>VTr = $N_p * \{ Ft * Ft_{sov} + Frs * Frs_{sov} \} * (1 - 1/AVORS)$</p>	<p>Change in running exhaust emissions due to speed improvement in HOV lanes.</p> <p>Change in running exhaust emissions in general purpose lanes as a result of vehicle shifted away from general purpose lanes.</p> <p>Reduction of emission from (auto start exhaust + auto running exhaust) from trip reduction.</p> <p>Reduction in daily automobile trips.</p>
--	--

Assumptions:	Source	Defaults		
AVORS: Average vehicle occupancy of rideshare (persons/vehicle)	COG Default	AVORS:	2.140	2.140
FRS: Percentage of people attracted to the HOV facility using ride share (decimal)	COG Default	FRS:	0.832	0.832
FRS,SOV: Percentage of people attracted to the HOV facility using ride share that previously were vehicle drivers (decimal)	COG Default	FRS,SOV:	0.561	0.561
FT: Percentage of people attracted to the HOV facility using a transit vehicle (decimal)	COG Default	FT:	0.143	0.143
FT,SOV: Percentage of people using a transit vehicle that previously were vehicle drivers (decimal)	COG Default	FT,SOV:	0.561	0.561
TLW: Average auto trip length (miles)	COG Default	TLW:	20	20.000
PG Annual Population Growth Rate assume 2.5%/Year	COG Default	PG	0.025	0.025
Volume Fraction: 24 Hour Volume to Peak hour Volume Fraction. (peak hour volume / 24 hour volume)	COG Default	VFC	0.380	0.380
VT_{RF} $(FT * FT_{SOV} + FRS * FRS_{SOV}) * (1 - 1/AVORS)$		VT_{RF}	0.291	0.291
Conversion Factor: Convert grams per mile of emissions to pounds per mile of emissions		Conversion Factor:	453.60	453.600

Variables:	Source			
V_H Daily Volume of HOV lane	Data management. DART Traffic Counts	V_H	20049	20049.000
V_Y Daily Volume Year		V_Y	2010	
Projected Daily Volume of HOV lane	Estimate	V_{HOV}	27638	27638
V_{GP,B} Volume of general purpose lane , before implementation of HOV.		V_{GP,B}		0.000
V_{GP,A} Volume of General purpose lane , after implementation of HOV.		V_{GP,A}		0.000
N_p Total number of expected people using the HOV lanes per day. If Restricted HOV use only peak our Volume [$N_p = 2.14 * V_{HOV}$]	Data management. DART Traffic Counts or calculated.	N_p	59145	59145
N_p = 2.14 * V_{HOV}				
L Center Line Miles	Project Specific	L	6.057	

4.0 High-Occupancy Vehicle Facilities

Emission Factors:	Speed		NO_x	VOC
TEF_{AUTO}: Auto trip-end emission factor (NO _x , VOC, or CO) (grams/trip)		TEF_{AUTO}:	0.37	0.47
EF: Speed-based running exhaust emission factor before implementation of HOV facility (NO _x , VOC, or CO) (grams/mile) (assume 43 mph, Light Duty Vehicles on fwy)	43mph	EF_B:	0.06	0.02
EF_{H,A}: Speed-based running exhaust emission factor on HOV facility (NO _x , VOC, or CO) (estimate) (assume 51 mph, Light Duty Vehicles on fwy)	51mph	EF_{H,A}:	0.06	0.02
EF_{GP,A}: Speed-based running exhaust emission factor after implementation of HOV facility (NO _x , VOC, or CO) (general purpose lanes) (estimate) (assume 43 mph, Light Duty Vehicles on fwy)	43mph	EF_{GP,A}:	0.06	0.02

Emission Calculations:			NO_x	VOC
A = V_{H,A} * (EF_B - EF_{H,A}) * L	Change in running exhaust emissions from vehicles shifting from general purpose lanes to HOV lanes	A:	0.000	0.000
B = (V_{GP,B} * EF_B - V_{GP,A} * EF_{GP,A}) * L	Change in running exhaust emissions of vehicles in general purpose lanes as a result of vehicles shifted away from general purpose lanes [assume negligible]	[B ≈ 0]	B: 0.000	0.000
C = VT_R [TEF_{AUTO} + EF_B * TLW]	Reduction in Emissions from Trip reduction-including auto start exhaust emissions and running exhaust emission from the entire trip	[C = (Np * VT_{RF}) * (TEF + EF_B * TLW)]	C: 27056.707	14993.207
VT_R = N_p * (F_T * F_{T,SOV} + F_{RS} * F_{RS,SOV}) * (1 - 1/AVO_{RS})	Reduction in daily Automobile Vehicle trips	[VT_R = N_p * VT_{RF}]	unit of measure: grams/Day	grams/day
			VT_R: 17233.5717	17233.5717

Results:		NO_x	VOC
Daily Emission Reduction = (A + B + C) / Conversion Factor	Daily Emission Reduction (lbs/day) =	59.65	33.05
Daily Emission Reduction = (A + B + C) / Conversion Factor	Daily Emission Reduction (tons/day) =	0.03	0.02

Source: The Texas Guide to Accepted Mobile Source Emission Reduction, August 2007

Shading denotes input variables specific to the project. Other variables are either standard for the program or calculated using these inputs.

Blue - Project Specific Input

Yellow - Assumptions

Green - Emission Factors

Speed and average volume on general-purpose lanes before and after implementation of the HOV facility are equal for part B. Local assumptions are calculated

5.0 Employer-Based Transportation Management Programs

5.1 Transit/Rideshare Services - Vanpools

Strategy: Reduction of vehicle trips and emissions through increased used of transit, carpooling, or vanpooling.

Project Year: 2023

Description: Employers or groups of employers in activity centers provide transportation service to and from the work site to transit facilities and homes. The services can include subscription buses, midday and park-and-ride shuttles, and Guaranteed Ride Home programs.

Project Description:

Application: Large companies or groups of cooperating businesses.

Project Code: 11048

Variables:		NO _x	VOC
EF_A: Speed-based running exhaust emission factor after implementation (NO _x or VOC) (grams/mile) (assume 34 mph, Light Duty Vehicle on all roadway types)	EF_A:	0.11	0.04
EF_B: Speed-based running exhaust emission factor before implementation (NO _x or VOC) (grams/mile) (assume 34 mph, Light Duty Vehicle on all roadway types)	EF_B:	0.11	0.04
N_{VA}: Number of vehicles after implementation (equal to number of vanpools)	N_{VA}:	83.00	83.00
N_{VOR}: Vehicle Occupancy	N_{VA}:	9.00	9.00
N_{VB}: Number of vehicles before implementation (equal to vanpool occupancy * number of vanpools)	N_{VB}:	747.00	747.00
TEF_{AUTO}: Auto trip-end emission factor (NO _x or VOC) (grams/trip)	TEF_{AUTO}:	0.37	0.47
TL_A: Average auto trip length after implementation (miles)	TL_A:	85.00	85.00
TL_B: Average auto trip length before implementation (miles)	TL_B:	35.00	35.00
VT_A: Vehicle trips after implementation	VT_A:	166.00	166.00
VT_B: Vehicle trips before implementation	VT_B:	1494.00	1494.00
Conversion Factor: Convert grams per mile of emissions to pounds per mile of emissions	Conversion Factor:	453.60	453.60
Equation:		NO _x	VOC
A = VT_B * TL_B * EF_B Auto running exhaust emissions before strategy implementation	A:	5751.90	2091.60
B = VT_A * TL_A * EF_A Auto running exhaust emissions after strategy implementation	B:	1552.10	564.40
C = (VT_B - VT_A) * TEF_{AUTO} Reduction in start exhaust emissions from reduction in vehicle trips to/from employment center	C:	491.36	624.16
Modified from the following Source: The Texas Guide to Accepted Mobile Source Emission Reduction Strategies, August 2007			
VT_A = N_{VA} * 2 trips/day Number of vehicles before or after strategy implementation multiplied by two trips per day (round trip).	VT_A:	166.00	166.00
VT_B = N_{VB} * 2 trips/day	VT_B:	1494.00	1494.00

Results:		NO _x	VOC
Daily Emission Reduction = [(A - B) + C] / Conversion Factor	Daily Emission Reduction (lbs/day) =	10.34	4.74
	Daily Emission Reduction (tons/day) =	0.01	0.00

Source: The Texas Guide to Accepted Mobile Source Emission Reduction Strategies, Texas Transportation Institute, August 2007

Local assumptions for vanpool projects are calculated from their monthly performance measures reported by the Dallas Area Rapid Transit and the Fort Worth Transit Authority for fiscal years 2004 to 2010. This analysis also incorporates an assumption of equal emission factors, trips, and trip length before and after implementation of the vanpool programs.

Shading denotes input variables specific to the project. Other variables are either standard for the program or calculated using these inputs.

Blue - Project Specific Input

Yellow - Assumptions

Green - Emission Factors

7.0 Traffic Flow Improvements -- TTI Equation

7.1 Traffic Signalization

Strategy: Traffic signalization projects can measurably reduce CO and HC emissions by decreasing vehicular stops and idling, which would in turn reduce travel times and traffic delays.

Project Year: 2023

Description: Traffic signalization increases the efficiency of traffic flow at intersections by improving interconnection and coordination of signals, leading to reductions in travel times, delays, and stop-and-go driving. Traffic signalization can be as simple as updating the equipment and/or software or improving the timing plan. Because signal improvements reduce travel times and stop-and-go driving conditions, they can measurably reduce CO and HC emissions as well as reducing fuel consumption.

Project Description: Level 1 Improvement: Basic Traffic Signal Retiming.

Application: Major arterials or high capacity roadways with uncoordinated traffic signals.

Project Code:

Variables:	Source		NO _x	VOC
EF_I: Idling emission factor (NO _x or VOC) (grams/mile) (equal to the emission factor at 2.5 mph for all vehicle types in all roadway).	MOVES3	EF_I:	1.01	0.43
EF_I: Idling emission factor (NO _x or VOC) (grams/hour) (equal to the emission factor at 2.5 mph, multiplied by 2.5 miles to get units of grams/hour)		EF_I:	2.53	1.08
D_B: Time delay before project implementation (seconds)	COG Default	D_B:	31.00	31.00
D_A: Time delay after project implementation (seconds)	COG Default	D_A:	25.00	25.00
V: Bi-directional arterial volume for analysis period	Project Specific	V:	19,590	19,590
P,H_R Peak Hour Ration	COG Default	P,H_R	0.46	0.46
V_{D,P}: Average daily volume during the peak period		V_{D,P}:	9011.40	9011.40
V_{D,OP}: Average daily volume during the off-peak period		V_{D,OP}:	10578.60	10578.60
DR: Reduction in time delay (seconds)	COG Default	DR:	6.00	6.00
Conversion Factor: Convert grams per mile of emissions to pounds per mile of emissions	Standard	Conversion Factor:	453.60	453.60
Equation:			NO _x	VOC
A= (D_B - D_A) * EF_I Change in exhaust emissions from improved speed during the peak and off-peak periods. * V _{D,P}		A:	37.92	16.15
B= (D_B - D_A) * EF_I Change in idling exhaust emissions from improved traffic flow during the peak and off-peak periods. * V _{D,OP}		B:	44.52	18.95
Results:			NO _x	VOC
Daily Emission Reduction = (A + B)/Conversion Factor	Daily Emission Reduction (lbs/day) =		0.18	0.08
	Daily Emission Reduction (tons/day) =		0.00	0.00

Source: The Texas Guide to Accepted Mobile Source Emission Reduction, August 2007

Local variable calculations utilize data from the Highway Capacity Manual, and the Dallas-Fort Worth Travel Demand Model.

Shading denotes input variables specific to the project. Other variables are either standard for the program or calculated using these inputs.

Blue - Project Specific Input

Yellow - Assumptions

Green - Emission Factors

7.0 Traffic Flow Improvements -- TTI Equation

7.2 Traffic Operations: Intersection Improvements

Strategy: Reduce congestion in corridors and intersections, improving traffic speeds and reducing idling times, leading to lower emission and improved traffic system efficiency.

Project Year: 2023

Description: Traffic operation improvements, similar to traffic signalization improvements primary focus on reducing congestion on local and arterial streets by improving the systems efficiency. Generally, each action will improve traffic flow and safety. Many roadway changes require only signage and pavement marking changes with little new construction and are relatively quick to implement.

Project Description:

Application: Major arterials or high capacity roadways.

Project Code:

Variables:	Source		NO _x	VOC
EF _I : Idling emission factor (NO _x or VOC) (grams/mile) (equal to the emission factor at 2.5 mph)	MOVES3	EF _I :	1.01	0.43
EF _I : Idling emission factor (NO _x or VOC) (grams/hour) (equal to the emission factor at 2.5 mph, multiplied by 2.5 miles to get units of grams/hour)		EF _I :	2.53	1.08
D _B : Time delay before project implementation (seconds)	COG Default	D _B :	31.00	31.00
D _A : Time delay after project implementation (seconds)	COG Default	D _A :	25.00	25.00
V: Bi-directional arterial volume for analysis period	Project Specific	V:	19,590.00	19,590.00
P,H _R Peak Hour Ration	COG Default	P,H _R	0.46	0.46
V _{D,P} : Average daily volume during the peak period		V _{D,P} :	9011.40	9011.40
V _{D,OP} : Average daily volume during the off-peak period		V _{D,OP} :	10578.60	10578.60
DR: Reduction in time delay (seconds)	COG Default	DR:	6.00	6.00
Conversion Factor: Convert grams per mile of emissions to pounds per mile of emissions	Standard	Conversion Factor:	453.60	453.60
Equation:				
A= (D _B - D _A) * Change in exhaust emissions from improved speed EF _I * V _{D,P} during the peak and off-peak periods.		A:	37.92	16.15
B= (D _B - D _A) * Change in idling exhaust emissions from improved traffic flow during the peak and off-peak periods.		B:	44.52	18.95
Results:				
Daily Emission Reduction = (A + B)/Conversion Factor	Daily Emission Reduction (lbs/day) =		0.18	0.08
	Daily Emission Reduction (tons/day) =		0.00	0.00

Source: The Texas Guide to Accepted Mobile Source Emission Reduction, August 2007

Local variable calculations utilize data from the Highway Capacity Manual, and the Dallas-Fort Worth Travel Demand Model.

Shading denotes input variables specific to the project. Other variables are either standard for the program or calculated using these inputs.

Blue - Project Specific Input

Yellow - Assumptions

Green - Emission Factors

7.0 Traffic Flow Improvements

7.4 Intelligent Transportation Systems - Regional Benefits Calculation Methodology - 2023 Emissions

Reduction in Estimated Emissions in a County (NOx and VOC) = (Freeways + Toll roads + HOV Lanes Emissions) * (% Recurrent Congestion Eliminated) * (% ITS Coverage)

County	NO _x (tons/day)	VOC (tons/day)	% ITS Coverage	% Emission (Nonrecurrent) ¹	% Recurrent Congestion Eliminated		% Nonrecurrent Congestion Eliminated ¹
Collin	2.67	0.41	88%	N/A	5%		N/A
Dallas	13.27	2.17	87%	N/A	5%		N/A
Denton	2.71	0.38	89%	N/A	5%		N/A
Tarrant	7.11	1.24	88%	N/A	5%		N/A
Total	25.75	4.20					

	Collin	Dallas	Denton	Tarrant	Four County Total (tons/day)	Four County Total (lbs/day)
Reduction in Estimated NOX Emissions Caused by Peak Hour Nonrecurrent Congestion ¹	N/A	N/A	N/A	N/A	N/A	
Reduction in Estimated NOX Emissions Caused by Peak Hour Recurrent Congestion	0.12	0.58	0.12	0.31	1.13	2,255.77
Reduction in Estimated Total NOX Emissions Caused by Peak Hour Congestion	0.12	0.58	0.12	0.31	1.13	2,255.77
Reduction in Estimated VOC Emissions Caused by Peak Hour Nonrecurrent Congestion ¹	N/A	N/A	N/A	N/A	N/A	
Reduction in Estimated VOC Emissions Caused by Peak Hour Recurrent Congestion	0.02	0.09	0.02	0.05	0.18	368.04
Reduction in Estimated Total VOC Emissions Caused by Peak Hour Congestion	0.02	0.09	0.02	0.05	0.18	368.04

Note: The methodology doesn't include nonrecurring congestion or off-peak condition

7.0 Traffic Flow Improvements -- TTI Equation

7.5 Grade Separation (Road-Road)

Strategy: Reduce congestion in corridors by reducing idling times and leading to lower emissions and improved traffic system efficiency.

Project Year: 2023

Description: Grade Separations increases the efficiency of traffic flow at intersections by reduction in travel times, delays, and stop-and-go driving.

Project Description:

Application: Major arterials or high capacity roadways.

Project Code:

Variables:	Source		NO _x	VOC
EF_I : Idling emission factor (NOx or VOC) (grams/mile) (equal to the emission factor at 2.5 mph)	MOVES3	EF_I :	1.01	0.43
EF : Idling emission factor (NOx or VOC) (grams/hour) (equal to the emission factor at 2.5 mph, multiplied by 2.5 miles to get units of grams/hour)		EF_I :	2.53	1.08
D_B : Time delay before project implementation (seconds)	COG Default	D_B :	45.00	45.00
D_A : Time delay after project implementation (seconds)	COG Default	D_A :	0.00	0.00
V : Bi-directional arterial volume for analysis period	Project Specific	V :	94,685	94,685
P,H_R Peak Hour Ration	COG Default	P,H_R	0.46	0.46
V_{D,P} : Average daily volume during the peak period		V_{D,P} :	43555.10	43555.10
V_{D,OP} : Average daily volume during the off-peak period		V_{D,OP} :	51129.90	51129.90
DR : Reduction in time delay (seconds)	COG Default	DR :	45.00	45.00
Conversion Factor : Convert grams per mile of emissions to pounds per mile of emissions	Standard	Conversion Factor :	453.60	453.60
Equation:			NO_x	VOC
A = (D _B - D _A) * Change in exhaust emissions from improved speed EF _I * V _{D,P} during the peak and off-peak periods.		A :	1374.71	585.27
B = (D _B - D _A) * Change in idling exhaust emissions from improved traffic flow during the peak and off-peak periods.		B :	1613.79	687.06
Results:			NO_x	VOC
Daily Emission Reduction = (A + B)/Conversion Factor	Daily Emission Reduction (lbs/day) =		6.59	2.80
	Daily Emission Reduction (tons/day) =		0.00	0.00

Source: The Texas Guide to Accepted Mobile Source Emission Reduction, August 2007

Local variable calculations utilize data from the Highway Capacity Manual, and the Dallas-Fort Worth Travel Demand Model.

Shading denotes input variables specific to the project. Other variables are either standard for the program or calculated using these inputs.

Blue - Project Specific Input

Yellow - Assumptions

Green - Emission Factors

7.0 Traffic Flow Improvements

7.5 Railroad Grade Separation

Strategy: Grade separation of rail lines and arterial streets reduces congestion in corridors by reducing idling times and leading to lower emissions and improved traffic system efficiency.

Project Year: 2023

Description: Railroad grade separations remove periodic traffic delays on major roadways by raising or lowering either the rail line or the roadway and permitting more efficient flow of traffic at major rail crossings.

Project Description/Code:

Application: Arterials with delays cause by at-grade rail crossings.

Variables:	Source		NO _x	VOC
EF_I : Idling emission factor (NO _x or VOC) (grams/mile). (Emission factor at 2.5 mph).	MOVES3	EF_I :	1.01	0.43
EF_I : Idling emission factor (NO _x or VOC) (grams/hour) (equal to the emission factor at 2.5 mph, multiplied by 2.5 miles to get units of grams/hour)		EF_I :	2.53	1.08
t_C : Average amount of time rail crossing is closed due to train crossing (hours/crossing)	TRE	t_C :	0.025	0.025
t_H : Duration of analysis period (hours)		t_H :	24.00	24.00
t_F : Frequency of Train per analysis period.	TRE	t_F :	30.00	30.00
t_{H,C} : Hours per analysis period roadway is closed due to train crossing	TRE	t_{H,C} :	0.75	0.75
V : Bi-directional arterial volume for analysis period	TxDOT	V :	19,656.49	19,656.49
Conversion Factor : Convert grams per mile of emissions to pounds per mile of emissions	Standard	Conversion Factor :	453.60	453.60
Equation:			NO_x	VOC
A = $t_{H,C} / t_H * V$ The proportion of arterial traffic affected by rail crossing delays		A :	614.27	614.27
B = $t_C / 2 * EF_I$ The idling emissions resulting from affected traffic assumed to be idling half of the average time the roadway is closed per train crossing		B :	0.03	0.01
Results:			NO_x	VOC
Daily Emission Reduction = (A * B)/Conversion Factor	Daily Emission Reduction (lbs/day) =		0.04	0.02
	Daily Emission Reduction (tons/day) =		0.00	0.00

Source: The Texas Guide to Accepted Mobile Source Emission Reduction Strategies , August 2007

Local variable calculations utilize data from the Dallas-Fort Worth Regional Travel Model, Federal Railroad Administration, Union Pacific Railroad, the Association of American Railroads (Railroad Facts" 1999 Edition, the Trinity Railway Express June 2003 Schedule, and the Regional Rail Corridor Study Consultant Team: URS Corporation, Carter-Burgess, and Lonnie Blaydes Consulting.

Shading denotes input variables specific to the project. Other variables are either standard for the program or calculated using these inputs.

Blue - Project Specific Input

Yellow - Assumptions

Green - Emission Factors

8.0 Park-and-Ride/Fringe Parking

8.1 New Facilities

Strategy: Reduction of vehicle trips and VMT by enhancements of transit system and ridesharing.

Project Year: 2023

Description: Construction of new park-and-ride facilities in locations remote from the central city area or major business activity centers or on the fringes of major employment centers. Lots or garages are constructed adjacent to or very near transit facilities or heavily traveled corridors. These lots are designed to be conducive to several modes of transportation including pedestrian and bicycle facilities. New facilities will require coordination with other transportation agencies, and political and citizen groups.

Project Description:

Application: Cities with a population density great enough to warrant projects that encourage carpooling

Project Code:

Variables:	Source		NO _x	VOC
EF_B: Speed-based running exhaust emission factor before implementation (NO _x or VOC) (grams/mile) (<i>assume 34 mph, Light Duty Vehicles in all roadway types</i>)	MOVES3	EF_B:	0.11	0.04
N_{PK}: Number of parking spaces	Project Specific	N_{PK}:	499	499
U_P: Parking lot utilization rate (estimate)	COG Default	U_P:	0.85	0.85
TL_W: Average auto work trip length (miles)	COG Default	TL_W:	20.00	20.00
TL_{PR}: Average auto trip length from home to parking facility (miles)	COG Default	TL_{PR}:	4.00	4.00
Conversion Factor: Convert grams per mile of emissions to pounds per mile of emissions		Conversion Factor:	453.60	453.60
Results:			NO_x	VOC
Daily Emissions Reduction= $[N_{PK} * U_P * (TL_W - TL_{PR}) * EF_B * 2 \text{ trips/day}] / \text{Conversion Factor}$	Daily Emission Reduction (lbs/day) =		3.29	1.20
	Daily Emission Reduction (tons/day) =		0.00	0.00

Source: The Texas Guide to Accepted Mobile Source Emission Reduction Strategies, Texas Transportation Institute, August 2007.

Local assumptions are calculated from data generated by the Dallas-Fort Worth Regional Travel Model, and from professional judgment of the North Central Texas Council of Governments staff.

Shading denotes input variables specific to the project. Other variables are either standard for the program or calculated using these inputs.

Blue - Project Specific Input

Yellow - Assumptions

Green - Emission Factors

11.0 Bicycle and Pedestrian Programs

11.1 Bicycle and Pedestrian Lanes or Paths

Strategy: Replacement of vehicle trips and VMT with bicycle and pedestrian travel.

Project Year: 2023

Description: A wide variety of bicycle and pedestrian projects are available to practitioners for implementation in air quality mitigation efforts. Funding for these types of programs has increased dramatically under ISTEA and TEA-21. Examples of such projects include (but are not limited to): reallocation of right-of-way to accommodate bicycles and pedestrians, new trails, median refuges at key intersections, improved connections between residential areas and transit stops.

Project Description:

Application: Areas where travel distances (residential/work or retail sites, for example) are short enough for bicycle/ pedestrian travel to be practical.

Project Code:

Variables:	Source		NO _x	VOC
EF _B : Speed-based running exhaust emission factor for participants' trip before participating in the bike/pedestrian program (NO _x or VOC) (grams/mile) (assume 34 mph, LDV and arterial roadway types).	MOVES 3	EF _B :	0.06	0.02
TEF _{AUTO} : Auto trip-end emission factor (NO _x or VOC) (grams/trip)	MOVES 3	TEF _{AUTO} :	0.37	0.47
TL _B : Average auto trip length before implementation (miles)	COG default	TL _B :	1.00	1.00
N _{BW} : Number of trips utilizing the bike/pedestrian facility	Project Specific	N _{BW} :	2,020	2,020

Where, N_{BW} is calculated using bike needs indices (BNI) and pedestrian needs indices (PNI).

Conversion Factor: Convert grams per mile of emissions to pounds per mile of emissions

Conversion Factor: 453.6 453.6

Results:
Daily Emissions Reduction = (N_{BW} * TL_B * EF_B) + (N_{BW} * TEF_{AUTO})/ Conversion Factor

Daily Emission Reduction (lbs/day) = 1.91 2.18

Daily Emission Reduction (tons/day) = 0.00 0.00

Source: The Texas Guide to Accepted Mobile Source Emission Reduction Strategies, August 2007

Final Units of measure: grams/day.

Shading denotes input variables specific to the project. Other variables are either standard for the program or calculated using these inputs.

Blue - Project Specific Input

Yellow - Assumptions

Green - Emission Factors